



- QUAREX**
Resin + Mineral fillers + Coating
- 5 YEARS GUARANTEE**
- Anti-slip coating, DIN 51097.
- Coating with excellent resistance to hydrolysis.
- High coating UV resistant.
- SUPERIOR HARDNESS coating** (<0.01 mm according to UNE EN 14688; maximum allowed 0.1 mm).
- Antibacterial treatment R<2 ISO 22196.
- Special cuts available. It can be cut on site by diamond saw.
- Recessed, raised or on Quare feet installation. Consult installation manual.

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

47 kg/m²

(*) Maximum recommended cut. For other cuts, please consult us.



		A (mm)									
		900	1000	1100	1200	1300	1400	1500	1600	1700	1800
800	C	160	160	160	160	160	160	160	160	160	160
	H	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	300	100	200	300	100	200	300
900	C	160	160	160	160	160	160	160	160	160	160
	H	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	300	100	200	300	100	200	300
1000	C	160	160	160	160	160	160	160	160	160	160
	H	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	300	100	200	300	100	200	300
B (mm)		Y*	200	200	200	200	200	200	200	200	200

PIZARRA

A 900 - 1800 | B 800-1000



Class C / PN24 / Class 3

STANDARD COLOURS



SPECIAL COLOURS



RAL



NCS



WASTES

EXTRA FLAT SHOWER WASTE

Flow rate 35 l/mn
Height 54 mm



VERTICAL SHOWER WASTE

Flow rate 35 l/mn
Height 96 mm



HIGH FLOW SHOWER WASTE

Flow rate 50 l/mn
Height 80 mm



SLIM + SHOWER WASTE

Flow rate 27 l/mn
Height 56 mm



WASTE COVER

RESIN WASTE COVER IN PIZARRA FINISH (SLATE), COLOURED

