



47 kg/m²

Resin + Mineral fillers
+ Coating

5 YEARS
GUARANTEE

Anti-slip coating.
DIN 51097.

Coating with excellent
resistance to hydrolysis.

High coating
UV resistant.

SUPERIOR HARDNESS coating
(<0.01 mm according to UNE EN
14688; maximum allowed 0.1 mm).

Antibacterial treatment
R<2 ISO 22196.

Special cuts available.
It can be cut on site by
diamond saw

Recessed, raised or on Quare
feet installation. Consult
installation manual.

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

(*) Maximum recommended cut. For other cuts, please consult us.



PIZARRA

A 900 - 2100 | B 700-1200



Class C / PN24 / Class 3

		A (mm)												
		900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100
700	C	125	125	125	125	125	125	125	125	125	125	125	125	125
	H	25	25	25	25	27	27	27	27	30	30	35	35	35
	X*	0	100	200	300	200	300	200	300	200	300	100	200	300
800	Y*	0	0	0	0	0	0	0	0	0	0	0	0	0
	C	125	125	125	125	125	125	125	125	125	125	125	125	125
	H	25	25	25	25	27	27	27	27	30	30	35	35	35
900	X*	0	100	200	300	200	300	200	300	200	300	100	200	300
	Y*	50	50	50	50	50	50	50	50	50	50	50	50	50
	C	125	125	125	125	125	125	125	125	125	125	125	125	125
1000	H	25	25	25	25	27	27	27	30	30	30	35	35	35
	X*	0	100	200	300	100	200	300	100	200	300	100	200	300
	Y*	100	100	100	100	100	100	100	100	100	100	100	100	100
1100	C	125	125	125	125	125	125	125	125	125	125	125	125	125
	H	25	25	25	25	27	27	27	30	30	30	35	35	35
	X*	0	100	200	300	100	200	300	100	200	300	100	200	300
1200	Y*	50	50	50	50	50	50	50	50	50	50	50	50	50
	C	125	125	125	125	125	125	125	125	125	125	125	125	125
	H	25	25	25	25	27	27	27	30	30	30	35	35	35
1000	X*	0	100	200	300	100	200	300	100	200	300	100	200	300
	Y*	100	100	100	100	100	100	100	100	100	100	100	100	100
	C	125	125	125	125	125	125	125	125	125	125	125	125	125
1100	H	25	25	25	25	27	27	27	30	30	30	35	35	35
	X*	0	100	200	300	100	200	300	100	200	300	100	200	300
	Y*	50	50	50	50	50	50	50	50	50	50	50	50	50
1200	C	125	125	125	125	125	125	125	125	125	125	125	125	125
	H	25	25	25	25	27	27	27	30	30	30	35	35	35
	X*	0	100	200	300	100	200	300	100	200	300	100	200	300
1000	Y*	60	60	60	60	60	60	60	60	60	60	60	60	60



LISO

A 900-1800 | B 700-1000



Class B / PN 18 / Class 2

		A (mm)									
		900	1000	1100	1200	1300	1400	1500	1600	1700	1800
700	C	125	125	125	125	125	125	125	125	125	125
	H	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	300	100	200	300	100	200	300
800	Y*	0	0	0	0	0	0	0	0	0	0
	C	125	125	125	125	125	125	125	125	125	125
	H	30	30	30	30	30	30	30	30	30	30
900	X*	0	100	200	300	100	200	300	100	200	300
	Y*	50	50	50	50	50	50	50	50	50	50
	C	125	125	125	125	125	125	125	125	125	125
1000	H	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	300	100	200	300	100	200	300
	Y*	60	60	60	60	60	60	60	60	60	60

STANDARD COLOURS

PURE WHITE

CREMA

GREY

GREGE

SILK GREY

FANGO

MACCHIATO

TERRA

GRAFITE

ANTRACITE

BLACK

NATURAL WHITE
Only available
in Pizarra texture

WASTES

EXTRA FLAT
SHOWER WASTE

Flow rate 35 l/mn
Height 54 mm

VERTICAL
SHOWER WASTE

Flow rate 35 l/mn
Height 96 mm

HIGH FLOW
SHOWER WASTE

Flow rate 50 l/mn
Height 80 mm

SLIM +
SHOWER WASTE

Flow rate 27 l/mn
Height 56 mm

SPECIAL COLOURS

GOLD

FOSSIL

TERRACOTTA

RAL

213 RAL

NCS

1950 NCS

WASTE COVERS

SAME-COLOURED WASTE
IN RESIN WITH LISO TEXTURE

SAME-COLOURED WASTE IN
RESIN WITH PIZARRA TEXTURE