



 Resin + Mineral fillers + Coating	 5 YEARS GUARANTEE	 Anti-slip coating. DIN 51097.	 Coating with excellent resistance to hydrolysis.	 High coating UV resistant.
 SUPERIOR HARDNESS coating (<0.01 mm according to UNE EN 14688; maximum allowed 0.1 mm).	 Antibacterial treatment R<2 ISO 22196.	 Special cuts available. It can be cut on site by diamond saw.	 Recessed, raised or on Quare feet installation. Consult installation manual.	

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

(*) Maximum recommended cut. For other cuts, please consult us.



		A (mm)							
		1100	1200	1300	1400	1500	1600	1700	1800
1100	C	550	600	650	700	750	800	850	900
	H	25	25	25	25	28	28	28	28
	X*	50	100	100	150	50	100	150	200
	Y*	50	50	50	50	50	50	50	50
1200	C	550	600	650	700	750	800	850	900
	H	25	25	25	25	28	28	28	28
	X*	50	100	100	150	50	100	150	200
	Y*	100	100	100	100	100	100	100	100
1300	C	550	600	650	700	750	800	850	900
	H	25	25	25	25	28	28	28	28
	X*	0	50	100	150	50	100	150	200
	Y*	150	150	150	150	150	150	150	150

PIZARRA

A 1001-1800 | B 1100-1300



Class C / PN24 / Class 3

STANDARD COLOURS



SPECIAL COLOURS



RAL



NCS



PRINT



WASTES

EXTRA FLAT SHOWER WASTE

Flow rate 35 l/mn
Height 54 mm



VERTICAL SHOWER WASTE

Flow rate 35 l/mn
Height 96 mm



HIGH FLOW SHOWER WASTE

Flow rate 50 l/mn
Height 80 mm



SLIM + SHOWER WASTE

Flow rate 27 l/mn
Height 56 mm



GRIDS

Stainless steel grid



Coloured stainless steel grid



Coloured grid, Pizarra texture



PVD



BLACK GLOSSY



TITANIUM GLOSSY



GOLD GLOSSY



COPPER GLOSSY

